

Caliber: **.44Special.**

Barrel length: 6".

Powder: **Ramshot - COMPETITION®.**

Bullet weight: 200 grains.

Start load: 4.0 grains (ca 725 Fps)

Maximum load: 4.7 grains (ca 825 Fps).

Bullet weight: 230-240 grains.

Start load: 3.7 grains (ca 675 Fps)

Maximum load: 4.4 grains (ca 750Fps).

Powder: **Ramshot - ZIP®.**

Bullet weight: 200 grains.

Start load: 5.0 grains (ca 725 Fps)

Maximum load: 6.0 grains (ca 825 Fps).

Bullet weight: 240 grains.

Start load: 4.0 grains (ca 650 Fps)

Maximum load: 5.0 grains (ca 725 Fps).

Powder: **Ramshot-TRUE BLUE®.**

Jacketed Bullets:

Bullet weight: 200 grains.

Start load: 7.0 grains (750 – 850 Fps) CA load.

Maximum load: 8.3 grains (875 – 975 Fps).

Bullet weight: 225 grains.

Start load: 6.5 grains (675 - 725 Fps)

Maximum load: 7.8 grains (775 – 825 Fps).

Bullet weight: 240 grains.

Start load: 6.0grains (650 - 750 Fps)

Maximum load: 7.0 grains (750 – 850 Fps).

Bullet weight: 250 grains.

Start load: 5.9 grains (650 - 750 Fps)

Maximum load: 6.6 grains (725 – 825 Fps).

Lead Bullets:

Bullet weight: 180 grains.

Start load: 7.4 grains (ca 775 Fps).

Maximum load: 8.8 grains (ca 950 Fps).

Bullet weight: 200 grains.

Start load: 6.7 grains (ca 725 Fps).

Maximum load: 8.0 grains (ca 850 Fps).

Bullet weight: 225 grains.

Start load: 6.5 grains (ca 675 Fps)

Maximum load: 7.5 grains (ca 775 Fps).

Bullet weight: 240 grains.

Start load: 5.6 grains (ca 625 Fps)

Maximum load: 6.7 grains (ca 725 Fps).

Bullet weight: 250 grains.

Start load: 5.4 grains (ca 600 Fps)

Maximum load: 6.5 grains (ca 700 Fps).

Lead Free Bullets:

Powder: **Ramshot-SILHOUETTE®.**

Bullet weight: 180 grains.

Start load: 8.2 grains (900 – 975 Fps).

Maximum load: 9.7 grains (1025-1100 Fps).

Bullet weight: 200grains.

Start load: 7.2 grains (775 – 825 Fps).

Maximum load: 8.5 grains (925-1025 Fps).

Bullet weight: 240grains.

Start load: 6.2 grains (675 - 725 Fps)

Maximum load: 7.2 grains (800 – 875 Fps).

Bullet weight: 250 grains.

Start load: 6.1 grains (650 - 750 Fps)

Maximum load: 6.8 grains (725 – 825 Fps).

NOTES:

It' important to note that SAFETY is our prime concern therefore we strongly recommend.

1. **ALWAYS BEGIN LOADING AT THE RECOMMENDED MINIMUM “START” LOAD and develop loads in 2% increments towards the MAXIMUM load.**
2. **CAUTION: Beware of double charging if the loading density is below 50% of the available volume.**
3. **If possible, measure the velocity and correlate with our data.**